



Now, with just one proxMagic® reader, it is able to read proven HID 125Khz and state-of-the art Mifare®, ISO15693 and iClass™ cards including many other card formats at both 125KHz and 13.56MHz on a single reader platform simultaneously providing the powerful capability for users to mix and match multiple card technologies in one single system. This technology also enables organizations to realize the long awaited advantages of smart cards transition for upgrading to a more powerful technology on a phased basis.

Supports the broadest range of proximity and smart card technologies in One Single Reader

The proxMagic® Multi-Technology Reader with IP65 rating offers a totally revolutionary new dimension in proximity technology. Proven 125KHz and 13.56MHz smartcard technologies are now combined in a single reader allowing card technologies to be mixed on the same access control system from different vendors. All known technologies are supported such as:

- HiTag
- Temic
- EM4002
- HID 125KHz
- Deister 125Khz
- ISO 14443A Serial Number
- Mifare®
- DESFire®
- ISO 14443B Serial Number
- ISO 15693 Serial Number
- iClass® Serial Number
- CASI RUSCO® ProxLite
- Indala®



The proxMagic® Multi-Technology Reader is the ultimate dream comes true reader solution offering flexible approach for supporting the broadest range of proximity and smart card technologies in the industry. This new breakthrough proxMagic® Multi-Technology Reader is most ideal for situations where a customer has an existing card population but also needs to upgrade or implement multifunction secure smartcard technologies on the same access control system without compromising on costs, integration, inter-operability and security.